

SECTION 10426/a
SIGNS

PART 1 - GENERAL

1.01 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.02 SUMMARY

- A. This section includes the following types of signs:
Tactile Plaque Signs, IU Sign Types A-G & K-L

1.03 SUBMITTALS

- A. **General:** Submit the following in accordance with Conditions of the Contract and Division 1 Specification Sections.
- B. **Product Data:** Include Manufacturer's construction details relative to materials, dimensions of individual components, profiles, and finishes for each type of sign required.

1.04 QUALITY ASSURANCE

- A. **Single Source Responsibility:** For each separate type of sign required, obtain signs from one source from a single manufacturer.
- B. **Design Criteria:** the Drawings indicate size, profiles, dimensional requirements, and graphics layout of signs and are based on the specific type and model indicated.

Signs by other manufacturers may be considered provided that deviations in dimensions and profiles are minor and do not change the design concept as judged by the University Architect's Office. The burden of proof of equality is on the proposer.

1.05 DELIVERY, STORAGE & HANDLING

- A. Deliver components correctly packed to prevent damage.
- B. Store in secure areas, out of weather and protected from work of other trades.

1.06 WARRANTY

- A. Provide Manufacturer's standard two year limited warranty covering manufacturing defects.

PART 2 - PRODUCTS

2.01 MANUFACTURER

- A. ASI Sign Systems, 2017 W. 18th St., Indianapolis, IN 46202.
- B. Sign Solutions, 121 Crossroads Dr., Whiteland, IN 46184.

- C. I.U. Physical Plant, 700 N. Walnut Grove, Bloomington, IN 47405.

2.02 MATERIALS

- A. Sign Plaque Material: polymid resin
- B. Laminating Base: 0.010" thick polyester laminated to 1/8" thick back acrylic.
- C. Fastener: .030" thick double face tape.

2.03 DIMENSIONAL PLAQUE SIGNS

- A. Manufacturer's standard monolithic tactile plaque sign construction. To meet relevant ADA regulations and requirements indicated for materials, thickness, finish colors, designs shapes, sizes and details of construction. Installed dimensional tolerances to be plus/minus 1/16 inch. Plaque color to be white.
- B. Graphics: Sign header copy to be raised 1/32" min. Helvetica Medium Uppercase from plaque first surface by Manufacturer's embossing process. Precisely formed, uniformly opaque graphics to comply with the relevant ADA regulations and the requirements indicated for size, style, spacing, content, position and colors. Body copy to be Helvetica medium, upper and lower case, sized as prepared on standard. Body copy shall be color black.
- C. Braille: Braille to be relieved 1/32" min. from plaque first surface by Manufacturer's embossing process. Precisely formed, uniformly opaque Braille to meet relevant ADA regulations and the requirements indicated for size, style, spacing, content, position and colors. Translation of sign copy to be the responsibility of the Manufacturer.
- D. Surface Texture: matte.

PART 3 - EXECUTION

3.01 INSTALLATION

- A. **General:** Locate plaque according to ADA guidelines, following IU standards, using installation methods in compliance with the manufacturer's instructions.
 - 1. Install signage adjacent to latch side of door at 2 inches off jamb to edge of sign and at 61 inches A.F.F. to top edge of sign.
- B. **Cleaning and Protection:** Upon completion of the installation, clean surfaces in accordance with the manufacturer's instructions. Protect units from damage until acceptance by the Owner.

END OF SECTION